

GIXER 250 MOTOGP

TECHNICAL SPECIFICATIONS

ENGINE

Engine Type:	4-Stroke, 1-Cylinder, Oil-Cooled
Valve System:	SOHC, 4 Valve
Displacement:	249 cm ³
Bore x Stroke:	76.0 mm x 54.9 mm
Engine Output:	26.5ps@9000rpm
Torque:	22.6Nm@7500rpm
Fuel System:	Fuel Injection
Starter System:	Electric
Transmission Type:	6 Speed, MT

DIMENSIONS AND WEIGHT

Wheels:	Alloy (Cast)
Overall Length:	2010 mm
Overall Width:	740 mm
Overall Height:	1035 mm
Wheel Base:	1345 mm
Ground Clearance:	165 mm
Seat Height:	800 mm
Kerb Mass:	161 kg
Fuel Tank:	12 L

BRAKE

Front:	Disc
Rear:	Disc

SUSPENSION

Front:	Telescopic, Coil Spring, Oil Damped
Rear:	Swing Arm Type, Mono Suspension

TYRE SIZE

Front:	110/70R - 17 M/C - Radial Tubeless
Rear:	150/60R - 17 M/C - Radial Tubeless

ELECTRICAL

Battery:	Maintenance-free, 12V 6Ah
Headlight:	LED
Tail light:	LED

GIXER 250

TECHNICAL SPECIFICATIONS

ENGINE

Engine Type:	4-Stroke, 1-Cylinder, Oil-cooled
Valve System:	SOHC, 4 Valve
Displacement:	249 cm ³
Bore x Stroke:	76.0 mm x 54.9 mm
Engine Output:	26.5ps@9000rpm
Torque:	22.6Nm@7500rpm
Fuel System:	Fuel Injection
Starter System:	Electric
Transmission Type:	6 Speed, MT

DIMENSIONS AND WEIGHT

Wheels:	Alloy (Cast)
Overall Length:	2010mm
Overall Width:	740mm
Overall Height:	1035mm
Wheel Base:	1345mm
Ground Clearance:	165mm
Seat Height:	800mm
Kerb Mass:	161kg
Fuel Tank:	12 L

BRAKE

Front:	Disc
Rear:	Disc

SUSPENSION

Front:	Telescopic, Coil Spring, Oil Damped
Rear:	Swing Arm Type, Mono Suspension

TYRE SIZE

Front:	110/70R - 17 M/C - Radial Tubeless
Rear:	150/60R - 17 M/C - Radial Tubeless

ELECTRICAL

Battery:	Maintenance-free, 12V 6Ah
Headlight:	LED
Tail light:	LED

GIXER 250

TECHNICAL SPECIFICATIONS

ENGINE

Engine Type:	4-Stroke, 1-Cylinder, Oil-Cooled
Valve System:	SOHC, 4 Valve
Displacement:	249 cm ³
Bore x Stroke:	76.0 mm x 54.9 mm
Engine Output:	26.5ps@9000rpm
Torque:	22.6Nm@7500rpm
Fuel System:	Fuel Injection
Starter System:	Electric
Transmission Type:	6 Speed, MT

DIMENSIONS AND WEIGHT

Wheels:	Alloy (Cast)
Overall Length:	2010 mm
Overall Width:	805 mm
Overall Height:	1035 mm
Wheel Base:	1340 mm
Ground Clearance:	165 mm
Seat Height:	800 mm
Kerb Mass:	156 kg
Fuel Tank:	12 L

BRAKE

Front:	Disc
Rear:	Disc

SUSPENSION

Front:	Telescopic, Coil Spring, Oil Damped
Rear:	Swing Arm Type, Mono Suspension

TYRE SIZE

Front:	110/70R - 17 M/C - Radial Tubeless
Rear:	150/60R - 17 M/C - Radial Tubeless

ELECTRICAL

Battery:	Maintenance-free, 12V 6Ah
Headlight:	LED
Tail light:	LED



Authorized Distributors for Suzuki Motor Corporation
ISO CERTIFIED COMPANY
Bhimsenthan, Paropakar Marg, 4233279, 4233280

AUTHORIZED DEALER



60,000 km
(scooter)
70,000 km
(Bikes)

The specifications and design of motorcycles shown here may vary according to the requirements and are subject to change without prior notice. Colours shown may not match the actual colours due to printing limitations