

# All New **ACCESS**

## The No Problem Ride



New Iconic Position Lamp



One Way Clutch



Long Floor Board



External Fuel Lid



### SUPERIOR ACCELERATION

Ideal Combustion Efficiency

High Compression Ratio

### LOW FUEL CONSUMPTION

Low Friction And Mechanical Loss

Light, Compact Engine Design

Optimised CVT Settings



#### STANDARD EDITION



#### SPECIAL EDITION



#### RIDE CONNECT EDITION



### Engine

Type	4-Stroke, 1-Cylinder, Air Cooled
Valve System	SOHC, 2-Valve
Displacement	124 cm <sup>3</sup>
Bore x Stroke (mm)	52.5 x 57.4 mm
Engine Output	6.2 kW @ 6500 rpm
Torque	10.2 Nm @ 5000 rpm
Fuel System	Fuel Injection
Starter System	Kick & Electric
Transmission Type	CVT

### Dimensions and Weight

Overall Length	1835 mm
Overall Width	680 mm (Std) 690 mm (SE/RC)
Overall Height	1155 mm
Wheelbase	1260 mm
Ground Clearance	160 mm
Seat Length	856 mm
Kerb Mass	106 kg (Std) 105 kg (SE/RC)
Wheels	Alloy/Cast
Fuel Tank	5.3 L

### Suspension

Front	Telescopic
Rear	Swing Arm

### Tyre Size

Front	90/90-12 54J
Rear	90/100-10 53J

### Brake

Front	Drum/Disc
Rear	Drum

### Electrical

Battery	Maintenance-free 12V, 4Ah
Headlight	LED
Tail Lamp	LED

### V.G. Automobiles Pvt. Ltd.

Authorized Distributors for Suzuki Motor Corporation,  
Naxal - 1, Kathmandu  
For Service Enquiry : 9801344312  
For Spare Parts Enquiry : 9801311264  
Office : 01-5913058/59

### AUTHORIZED DEALER



60,000 km  
(Scooter)  
70,000 km  
(Motorcycle)

[f SuzukiMotorcycleNepal](#)

[Instagram SuzukiMotorcycleNepal](#)

[TikTok SuzukiMotorcycleNepal](#)

[www.suzukimotorcycle.com.np](http://www.suzukimotorcycle.com.np)

The specification and design of scooter shown here may vary according to the requirements and are subject to change without prior notice, Colours shown may not match the actual colours due to printing limitations.